

NO U DISTRIBUTION SYSTEM

CENTRAL POWER DISTRIBUTION TO REMOTE MODULES

PRODUCT OVERVIEW

The No U Distribution System comprises of a central distribution box and up to 4 remote socket modules.

The distribution box can be mounted between the side rails of a rack or directly as a 19" unit. Remote modules can be mounted vertically on the rack uprights.

Central Distribution Unit

Will accept up to 32A supply via a fixed 4sqmm cable, terminated with a 32A commando plug. The unit is supplied with mounting brackets for both side mounting (No u) or 19" rack mount ears. The top (Front) face supports a 32A double pole input breaker and 4 off 16A circuit breakers, 1 for each of the remote modules together with a mains present neon indicator. The bottom (Rear) face supports 4 off 16A twist lock mains connectors supplying each remote module.

Remote Socket Module

Each remote contains 6 off IEC 320 C13 connectors and a power present neon indicator. The remote is connected to the distribution box via a 2m 16A umbilical terminated with a matching twist lock connector (Other lengths by request) Each remote can be secured to the rack by its integral mounting brackets.



Specifications

Central Distribution Unit

Max. Current	32A
AC Voltage	200-240v
Frequency	50/60Hz
Load Capacity	7360VA @230v
Input Protection	32A MCB
Output Protection	10A MCB per channel
Overload Protection	Yes
Indicator Light	Neon

Remote Outlet Module

Max. Current Rating	16A
AC Voltage	200-240v
Frequency	50/60Hz
Max. Current (per socket)	10A
Indicator Light	Neon

Part Number	Description
EDP-PMS-NOU-M	Master Unit to take up to 4 remote modules
EDP-PMS-NOU-R	Remote module 6 IEC 320 C13 outlets

Options.

- Additional length cables available to order.