

RAISED FLOOR GROOMETTS

KoldLok® raised floor grommets are the leading solution for sealing cable openings in raised floor environments. KoldLok® grommets are designed to virtually eliminate bypass airflow, increase cooling capacity, enable higher density, and dramatically lower energy consumption.

The KoldLok® Range

KoldLok® 4" Round - P/N: 46-40001



- 4" Round KoldLok grommet that combines brush and membrane for highly efficient seal.
- Split design allows installation in existing 4" round openings.
- Overall size - 143mm x 48mm.
- Usable cable area 244mm².
- Hole cut diameter 102mm.

KoldLok® 6" Round - P/N: 46-40003



- 6" Round KoldLok grommet that combines brush and membrane for highly efficient seal.
- Split design allows installation in existing 6" round openings.
- Overall size - 192mm x 48mm.
- Usable cable area 573mm².
- Hole cut diameter 152mm.

KoldLok® Mini - P/N: 46-1000-10077



- Designed to seal small 6" x 4" cable openings.
- Single layer of angled brushes.
- Split design.
- Overall size - 195mm x 144mm x 38mm.
- Usable cable size - 127mm x 64mm.

KoldLok® Integral - P/N: 46-1000-1010



- Double layer brush grommet designed for sealing new cable openings in raised floors.
- Optional metal safety plate P/N: 46-5000-SP.
- Overall size - 279mm x 210mm x 41mm.
- Usable cable size - 203mm x 102mm.

KoldLok® Split Integral - P/N: 46-1000-3030



- Double layer brush grommet designed for sealing new cable openings in raised floors.
- Optional metal safety plate P/N: 46-5000-SP2.
- Overall size - 279mm x 210mm x 41mm.
- Usable cable size - 203mm x 102mm.

KoldLok® Surface - P/N: 46-2000-2020



- Double layer brush grommet with split design for sealing existing cable openings in raised floors.
- Overall size - 279mm x 210mm x 29mm.
- Maximum cutout size sealed - 254mm x 184mm.
- Usable cable size - 210mm x 102mm.

KoldLok® Surface L - P/N: 46-2000-2030



- Double layer brush grommet with split design for sealing existing cable openings in raised floors.
- Metal plates extend the size of the opening sealed.
- Overall size - 305mm x 298mm x 33mm.
- Maximum cutout size sealed - 254mm x 248mm.
- Usable cable size - 210mm x 102mm.

KoldLok® Surface XL - P/N: 46-2000-2040



- Double layer brush grommet with split design for sealing existing cable openings in raised floors.
- Metal plates extend the size of the opening sealed.
- Overall size - 305mm x 381mm x 33mm.
- Maximum cutout size sealed - 254mm x 330mm.
- Usable cable size - 210mm x 102mm.

KoldLok® 3" Extended - P/N: 46-4000-10012



- Double layer brush grommet designed to seal larger openings and perimeter openings.
- Compatible with both 24" and 600mm floor tiles.
- Also available in 60" length P/N: 46-4000-10097.
- Overall size - 610mm x 128mm.
- Maximum cutout size sealed - 610mm x 102mm.
- Usable cable size - 559mm x 64mm.

KoldLok® 6" Extended - P/N: 46-4000-10013



- Double layer brush grommet designed to seal larger openings and perimeter openings.
- Compatible with both 24" and 600mm floor tiles.
- Also available in 60" length P/N: 46-4000-10098.
- Overall size - 610mm x 205mm.
- Maximum cutout size sealed - 610mm x 178mm.
- Usable cable size - 559mm x 140mm.

KoldLok® SplitLok™ - P/N: 46-4040 & 46-5050



- Interlocking split frame with smooth polished surface.
- Easier installation reduces installation labour.
- Stronger material – better strength.
- Dry erase markable surface for better identification.
- Integral (46-4040) overall size: 279mm x 212mm x 42mm
- Square (46-5050) overall size: 191mm x 188mm x 42mm
- Optional safety covers P/N: 46-10187 (4040) & 46-10191 (5050).

Ver: EDPKLR0623.1